

rag square-5¼"



## raggy GO! FLOOR PILLOW

finished size 24¾" x 24¾"




### FABRIC AND CUTTING REQUIREMENTS

- Yardage based on 40" wide fabric
- 1¾ yards, cut 56 rag squares
- 1¾ yards, cut 42 rag squares
- ¾ yard fabric for pillow backing
- 2—24 oz. bags polyester fiberfill

### SEWING DIRECTIONS

1. Layer two rag squares of the same fabric right sides up.
2. Sew an "X" through layered squares as shown in first square of diagram. Reinforce stitching at beginning and end of each line of stitching.
3. Make 28 green and 21 blue layered rag squares.
4. Layout layered squares according to diagram.
5. Place a strip of blue painters tape 1" to the right of machine needle to use as a guide for sewing the 1" seam allowance.
6. Pin and sew squares together in horizontal rows using 1" seam allowance and a slightly shorter stitch length (2.0).



7. Press seams open.
  8. Pin and sew rows together to complete pillow top.
  9. Press seams open.
  10. Measure pillow top.
  11. Cut backing fabric to this measurement.
  12. Layer pillow top wrong sides together overbacking fabric.
  13. Pin edges.
  14. Topstitch 1" around perimeter of pillow. Leave 6" opening for stuffing.
- Optional: By hand, cut fringe to match pillow front in the seam allowance of the pillow back.*
15. Launder to "bloom," remembering to empty lint screen frequently.
  16. Stuff with polyester fiberfill.
  17. Topstitch or hand stitch opening closed.

